Louisiana Department of Natural Resources Solar Energy Workshop **Preservation Resource Center** New Orleans, LA January 24, 2007 Presented by: Peter DeNapoli SolarWorld peter.denapoli@solarworld-usa.com



- Who We Are?
- What Is The Technology?
- What Does It Look Like?
- What Is the Investment?

SOLARWORLD



SolarWorld Overview

- Over 29 years experience in PV
- World's 3rd largest PV company, largest US
- Formally: Arco Solar, Siemens Solar, Shell Solar Acquired 100% of Shell Solar (July 2006):
- Only business is PV
- Vertically integrated (cradle to grave)
- Mono, Multi CZ
- 200+ MW production capacity global
- 80+ MW production capacity US



Strategy of vertical integration of the solar value chain.

silicon procuremen	t wafer producti	on cell production	n module produc	tion trading
Joint Solar Silicon GmbH & Co. KG @Mishardolding* Deutsche Solar AG Business Unit: "Solar Material"	Deutsche Solar AG RGS Development BV Deutsche Solar AG1 33% phareholding*	Deutsche Cell GmbH	Solar Factory GmbH GPV (Gällivare PhotoVoltaic AB)	SolarWorld AG SolarWorld California Inc. SolarWorld Ibérica S.L. Solarparc AG 29%shardolding*

^{*} as at the cutoff date of 31 March 2006 All other companies are wholly-owned subsidiaries of the SolarWorld AO



Where we came from. Off-grid remote power.



Wireless Power for Wireless
Communications





Portable Power ITS and Traffic





What we do today.



World PV Market



Market By Application MW

Application	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005
Consumer Products	22	26	30	35	40	45	60	65	70	75
U.S. Off-Grid	8	9	10	13	15	19	20	25	25	35
World Off-Grid Rural	15	19	24	31	38	45	60	75	80	90
Communications and Signal	23	28	31	35	40	46	60	75	80	95
OFF-GRID COMMERCIAL	12	16	20	25	30	36	45	50	60	70
Grid-Connected Res/Commercial	7	27	36	60	120	199	270	360	650	1100
Central >100KW (AC)	2	2	2	2	5	5	5	8	20	60
Total (MW)	89	126	153	201	288	395	520	658	980	1525
CUMULATIVE	289	415	568	769	1057	1452	1972	2530	3610	5135

Source: Paul Maycock



Definitions



CELL

Basic building block of a module.



MODULE

Smallest unit that can do real-world work; building block in the field.



PANEL

Modules connected together.



ARRAY

Panels mounted to structure.



Technology Overview

Crystal Growing

Polysilicon Sort , Etch & Pack



Crystal Growing



Ingot Shaping



Wafering


Wafer Slicing



Clean & Etch



SEM of Wafer Surface



Cell Fabrication

Diffusion & Oxidation



Front & Rear Metalization



Cell Test



Module Assembly

Cell Stringing



Lay Up & Lamination




Module Assembly & Test





Technology Overview - Cells




Untreated cell

TOPSTM surface treatment improves efficiency by trapping more light and creating a greater active surface area



Technology Overview - Cells

- Crystalline cells 125mm x 125mm ("5 Inch")
- TOPSTM
 Patented micro-texturisation of the cell surface called TOPSTM (Texture Optimised Pyramidal Surface) to improve light capture & cell efficiency.
- Enhanced "back-surface field" enhances the electricity generating capacity of the cell – delivering more power for the same amount of light trapped in the cell.
- New silicon nitride anti-reflection coating traps more light than coatings previously used resulting in 10% higher cell efficiency.



TOPSTM produces ultra-fine light capturing pyramids.



System Overview - Three Main Components



Modules



Mounts



Inverters (Power Controls)



Technology Overview - Modules






SolarWorld California 4650 Adohr Lane Camarillo, CA 93012 800-94-SOLAR E-Mail: service@solarworld-usa.com www.solarworld-usa.com




SolarWorld Module SW 165/175 mono

erformance under standard test conditions (ST	τ)	Component materials			
eak power (Pmax) Aaximum power point voltage (Vmpp) Aaximum power point current (Impp) Open circuit voltage (Voc)	165 Wp 34.4 V 4.8 A 43.3 V	175 Wp 35.7 V 4.9 A 44.4 V	Cells per module Solar cells Cell dimensions Thermal characteristics	monocrystalline silicon 125 x 125 mm (5 x 5 in)	
hort circuit current (Isc)	5.3 A	5.3 A	NOCT Pmpp temp coefficient Voc temp coefficient Vmp temp coefficient	45.5°C -0.43 %/ °C -145 mA/ °C -127 mV/ °C	
eak power (Pmax)	125 Wp	131 Wp	isc temp coefficient	1.4 mA/ °C	
Maximum power point voltage (Vmpp)	31.9 V	33.1 V	System design characteristics		
Aaximum power point current (Impp)	3.9 A	4.0 A	Maximum system voltage	600V (UL)	
Open circuit voltage (Voc)	40.1 V	41.2 V	Series fuse rating	15 A	
hort circuit current (Isc)	4.3 A	4.3 A	Rated power and maximum toler	ance	
Alnor reduction in efficiency under partial loa it 200 W/m², 92 % (+/- 3 %) of the STC efficien		STC Rated power PTC Rated power Quick Connector protection ratir Connector type	165/175 Wp +/- 3 % 149.1 Wprc / 158.3 Wprc ag (closed) IP 65 MC Type 4		










Technology Overview - Modules


- Low iron, water white tempered glass front
- EVA encapsulant layer
- Solar cell circuit
- Vinyl encapsulant layer
- Tedlar back sheet
- Anodized aluminum frame
- Cable Connectors (Gen3 for '07 NEC)
- 25 year warranty
- Wind load 120 mph
- UL, CEC, IEC, FSEC certified
- Power tolerance +/- 3%






Technology Overview - Modules


- A sealed box containing 'Golden Modules' are shipped in sequence to NREL, TÜV, Camarillo & Evora on an annual basis.
- Each 'Golden Module' is tested at each location 5x per day, over 6 different days for a total of 30 measurement.
- During each test the 'Golden Modules' have to be stabilised to a temperature of 25 +/-5 degrees centigrade.
- Measurements from each test facility are forwarded to SolarWorld's Quality Centre in Camarillo to analyse & determine the degree of correlation between SolarWorld's testing simulators & those of the National Laboratories.
- SolarWorld's testing simulators are then adjusted, if required, to ensure a high level of correlation with National Laboratories.





Technology Overview - Arrays








Technology Overview – Connectors & Mounts

























50 kW system

The total PV system has a 50.00 kW rating after accounting for losses and operating conditions</EM

This system has a net savings of \$9,735, produces 72,116 kWh of electricity per year, and eliminated 143,367 lbs of CO_2 , 571 lbs of SO_2 , and 274 lbs of NO_X emissions in the first year.

























212 kW system

The total PV system has a 212.00 kW rating after accounting for losses and operating conditions</EM

This system has a net savings of \$31,354, produces 288,465 kWh of electricity per year, and eliminated 573,468 lbs. of CO_2 , 2,285 lbs. of SO_2 , and 1,096 lbs. of NO_X emissions in the first year.



















The New Munich Trade Fair Centre



Architectural Beautification Through Solar Integration
























Why Solar Electric



Overview: Reasons for Using Solar





Three key elements for good financial investment.

- 1. Higher Electric Rates
- 2. Good Incentives
- 3. Customers, Communities Ready For Solar.

Current Incentives Available in Louisiana:

Federal tax credit: 30%

State of Louisiana: \$0.00

City of New Orleans: \$0.00



Solar Electricity by SolarWorld - 100 kW Example (Florida)

•	Installed Price	\$800,000
---	-----------------	-----------

- Less Federal Tax Credit (30%) (\$240,000)
- Less State Rebate (\$4.00/Watt Peak) (\$400,000)
- Net System Cost \$160,000
- Energy Savings (Accumulated Revenue 25 Years) \$543,773
- IRR (After Tax) 32%
- Payback period (Accounts for Depreciation) 2 years

Net System Cost if in LA \$560,000



A sound financial investment:

- 3-4 year payback (with incentives)
- Internal rates of return (IRR) over 20% are common
- 25+ years of free energy
- A 100 kW system can save you over \$500K in energy
- Hedge against rising and unpredictable energy costs



If you have been buying electricity for the past 10 years...

* You already made the investment (\$159,685.00)

- Federal tax credit 30%
- State incentive at \$4.00/watt,
- Electric rate of \$.10/kWh,
- Utility escalation of 3%/year,
- Inflation 1%



Thank you.
Peter DeNapoli
SolarWorld

peter.denapoli@solarworld-usa.com

www.solarworld-usa.com

Phone: 561-477-7679


SOLAR WORLD





What It Looks Like...





Tomorrow!

SolarWorld...

The right company.

The right technology!